

TECHNICAL DATA SHEET

Concrete Shield™ Enhancer - Premium

ISSUED: April 2014

INTRODUCTION

Concrete Shield™ Enhancer - Premium

Color enhancer and heavy duty sealing protection against most stains

USE

For use in warehouses, restaurants, retail shops and car parks.

FEATURES

Concrete Shield™ Enhancer - Premium

- Enriches Color
- Heavy duty protection against most stains
- Solvent-based, interior and exterior applications

APPLICATION

SURFACE PREPARATION

- **Concrete Shield™ Enhancer - Premium**
- Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results.
- Make sure surface is clean, free of waxes, coatings, and previous sealers, and is dry for 24–72 hours.
- Surface temperature should be between 10°C and 35°C. Ensure that the area is well-ventilated during application and until the surface is dry.
- Mask off any surfaces not intended to be treated.

EQUIPMENT FOR APPLICATION

- For small jobs, use a paint pad, roller, or brush.
- For larger jobs, use a pump-up garden sprayer available at your local garden center or hardware store.
- **PLEASE NOTE:** Do not use a power sprayer. Power sprayers create a significant amount of overspray, resulting in wasted product and the need for additional clean-up. A pump-up garden sprayer will reduce the potential for over-exposure to vapors and produce better results.

APPLICATION

- Apply **Concrete Shield™ Enhancer – Premium** liberally and evenly using a paint pad, roller, brush, or pump-up garden sprayer.
- **PLEASE NOTE:** Do not use a power sprayer, towel, or sponge for application. Do not thin before using.
- Allow sealer to penetrate surface for 15–20 minutes. Denser material may require more time to penetrate. **DO NOT ALLOW EXCESS SEALER TO DRY ON SURFACE.** Failure to remove excess sealer from surface may result in residue that may need to be mechanically removed.
- Thoroughly wipe surface with multiple dry cloths to remove all excess sealer. A second coat may be needed for more absorbent surfaces. If darker appearance is required, sealer should be applied one hour after initial application, as directed in steps 2 through 4. For wet look use **Concrete Shield™ Enhancer - Wet Look Sealer**
- Full cure is achieved after 24–72 hours. Avoid foot traffic for 6–8 hours after application.

CLEAN UP

- Clean equipment with mineral spirits promptly after the job is complete.
- **PLEASE NOTE:** Rags and equipment that are wet with product may be flammable.
- Clean equipment with mineral spirits and allow to dry in a well-ventilated area.

TECHNICAL DATA SHEET

SAFETY

Avoid contact with skin and eyes. Avoid contact with foodstuff and utensils. Wear protective clothing, gloves, goggles etc. In the event of contact with the eyes or mouth, wash with clean water and obtain medical attention immediately.

For further information, refer to the Fortis Material Safety Data Sheet and Technical Data Sheet. www.fortisadhesives.com.au

Disclaimer

Fortis products should be used in accordance with the information contained here. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained here is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings office directly. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained here